

Telephone: 03 9357 7524 Fax: 03 9357 7521 www.australiancrane.com.au



ACM 105SP SPECIFICATIONS

Overhead wire maintenance vehicle	Mercedes Benz Atego 1629 4x4 truck
Gross weight	16 ton GVM
Maximum working height	10.5 meters from rail level
Maximum outreach	7 meters
Basket (fully insulated)	2.5m x 2.0m, 450kgs capacity
Hetronic remote controller	

Speeds

Maximum speed on road	100km/hour
Maximum speed on rail	30km/hour
Maximum speed in work mode	10km/hour

Hi Rail

Hi Rail standard gauge	1,435mm	
Front bumper bar		
Tow bar assembly		

Wire boom support

Maximum height from the rail level	7.5m
Vertical swing capability of 30º either side of vertical	cal
Wire boom support head (insulated)	
Maximum load of 500kgs horizontally & 500kgs v	ertically at 6.5 meters height

Pantograph and recording package

Austbreck pantograph Pantograph recording device

Lighting
LED lighting in the basket
Ground lighting

Energy efficient work lighting for ground work

Adjustable directional lights on platform

Work modes

Stationary (No Hi Rail)	Outriggers fully extended
Hi Rail load chart walking	No outriggers
Hi Rail load chart stationary	Minimum outriggers deployed
Hi Rail load chart stationary	Outriggers deployed and fully extended

Safety Equipment

AS1418.10&EN 280 compliant

Boom anti-collision system Automatic speed control/reduction/soft stop system


Boom and basket/bucket automatic stowing system Emergency stop/emergency pump

Hyrdaulic cylinder lock valves/hydraulic safety valves
Outriggers indicator, lower controller

Load moment indicator
Emergency descent devices

PLATFORM RANGE CHART 360° ROTATION (WSB not available)

Blue Zone, Stationary mode (Outrigger down) Max platform reach: 7.1m + 1m arm





HEAD OFFICE:

42 Glenbarry Road, Campbellfield VIC 3061 Australia Tel: +61 (03) 9357 7524

Fax: +61 (03) 9357 7521

www.australiancrane.com.au